

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended

## Elastomastic™ TFN Comp. A

Version  
1.2

Revision Date:  
31.12.2024

Date of last issue: 31.10.2024  
Date of first issue: 15.12.2022

---

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

Trade name : Elastomastic™ TFN Comp. A  
Product code : 000000000000595559

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Sub-stance/Mixture : Coatings and paints, thinners, paint removers  
Recommended restrictions on use : Reserved for industrial and professional use.

#### 1.3 Details of the supplier of the safety data sheet

Company : Sherwin-Williams Coatings  
Deutschland GmbH  
Rieter Tal 1  
71665 Vaihingen / Enz  
Telephone : +4970421090  
E-mail address of person responsible for the SDS : SDS-DE@sherwin.com

#### 1.4 Emergency telephone

##### National advisory body/Poison Center

Telephone number: Not available

##### Supplier

Telephone number: +49 (0) 7042 109-0

Hours of operation: Emergency contact available 24 hours a day

---

### SECTION 2: Hazards identification

#### 2.1 Classification of the substance or mixture

##### Classification (REGULATION (EC) No 1272/2008)

Skin irritation, Category 2	H315: Causes skin irritation.
Eye irritation, Category 2	H319: Causes serious eye irritation.
Skin sensitization, Category 1	H317: May cause an allergic skin reaction.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended

## Elastomastic™ TFN Comp. A

Version  
1.2

Revision Date:  
31.12.2024

Date of last issue: 31.10.2024  
Date of first issue: 15.12.2022

Long-term (chronic) aquatic hazard, Category 2

H411: Toxic to aquatic life with long lasting effects.

### 2.2 Label elements

#### Labeling (REGULATION (EC) No 1272/2008)

Hazard pictograms :



Signal Word : Warning

Hazard Statements :  
H315 Causes skin irritation.  
H317 May cause an allergic skin reaction.  
H319 Causes serious eye irritation.  
H411 Toxic to aquatic life with long lasting effects.

Precautionary Statements : **Prevention:**  
P261 Avoid breathing mist or vapors.  
P264 Wash skin thoroughly after handling.  
P273 Avoid release to the environment.  
P280 Wear protective gloves/ eye protection/ face protection.  
**Response:**  
P333 + P313 If skin irritation or rash occurs: Get medical advice/ attention.  
P391 Collect spillage.

#### Hazardous ingredients which must be listed on the label:

bis-[4-(2,3-epoxipropoxy)phenyl]propane  
Reaction products of hexane-1,6-diol with 2-(chloromethyl)oxirane (1:2)  
Cashew, nutshell liq.  
reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight  $\leq 700$ )  
bisphenol-F-(epichlorhydrin) epoxy resin  
oxirane, mono[(C12-14-alkyloxy)methyl] derivs.

### 2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended

## Elastomastic™ TFN Comp. A

Version  
1.2

Revision Date:  
31.12.2024

Date of last issue: 31.10.2024  
Date of first issue: 15.12.2022

### SECTION 3: Composition/information on ingredients

#### 3.2 Mixtures

##### Components

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	Concentration (% w/w)
bis-[4-(2,3-epoxipropoxy)phenyl]propane	1675-54-3 216-823-5 603-073-00-2 01-2119456619-26-XXXX	Skin Irrit. 2; H315 Eye Irrit. 2; H319 Skin Sens. 1; H317 Aquatic Chronic 2; H411  specific concentration limit Eye Irrit. 2; H319 ≥ 5 % Skin Irrit. 2; H315 ≥ 5 %	≥ 30 - < 50
Reaction products of hexane-1,6-diol with 2-(chloromethyl)oxirane (1:2)	933999-84-9  01-2119463471-41-XXXX	Skin Irrit. 2; H315 Eye Irrit. 2; H319 Skin Sens. 1; H317 Aquatic Chronic 3; H412	≥ 2,5 - < 10
Cashew, nutshell liq.	8007-24-7 232-355-4 01-2119502450-57-XXXX	Acute Tox. 4; H302 Acute Tox. 4; H312 Skin Irrit. 2; H315 Eye Dam. 1; H318 Skin Sens. 1A; H317	≥ 1 - < 3
reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight ≤ 700)	25068-38-6 500-033-5 603-074-00-8 01-2119456619-26-XXXX	Eye Irrit. 2; H319 Skin Irrit. 2; H315 Skin Sens. 1; H317 Aquatic Chronic 2; H411  specific concentration limit Eye Irrit. 2; H319 ≥ 5 % Skin Irrit. 2; H315 ≥ 5 %	≥ 0,25 - < 1
bisphenol-F-(epichlorhydrin) epoxy resin	9003-36-5 500-006-8 01-2119454392-40-XXXX	Skin Irrit. 2; H315 Skin Sens. 1; H317 Aquatic Chronic 2; H411	≥ 0,1 - < 0,25
oxirane, mono[(C12-14-alkyloxy)methyl] derivs.	68609-97-2 271-846-8	Skin Irrit. 2; H315 Skin Sens. 1; H317	≥ 0,1 - < 0,3

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended

## Elastomastic™ TFN Comp. A

Version  
1.2

Revision Date:  
31.12.2024

Date of last issue: 31.10.2024  
Date of first issue: 15.12.2022

	603-103-00-4 01-2119485289-22- XXXX	Repr. 1B; H360F	
--	---	-----------------	--

For explanation of abbreviations see section 16.

### SECTION 4: First aid measures

#### 4.1 Description of first-aid measures

- General advice : Move out of dangerous area.  
Consult a physician.  
Show this material safety data sheet to the doctor in attendance.  
Do not leave the victim unattended.
- If inhaled : If unconscious, place in recovery position and seek medical advice.  
If symptoms persist, call a physician.
- In case of skin contact : If skin irritation persists, call a physician.  
If on skin, rinse well with water.  
If on clothes, remove clothes.
- In case of eye contact : Small amounts splashed into eyes can cause irreversible tissue damage and blindness.  
In the case of contact with eyes, rinse immediately with plenty of water and seek medical advice.  
Continue rinsing eyes during transport to hospital.  
Remove contact lenses.  
Protect unharmed eye.  
Keep eye wide open while rinsing.  
If eye irritation persists, consult a specialist.
- If swallowed : Keep respiratory tract clear.  
Do NOT induce vomiting.  
Do not give milk or alcoholic beverages.  
Never give anything by mouth to an unconscious person.  
If symptoms persist, call a physician.  
Take victim immediately to hospital.

#### 4.2 Most important symptoms and effects, both acute and delayed

- Symptoms : There are no data available on the mixture itself. Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS] See Sections 2 and 3 for details.  
Exposure to component solvent vapour concentrations in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and, in extreme cases, loss of consciousness. Solvents may cause some of the above effects by absorption through the

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended

## Elastomastic™ TFN Comp. A

Version  
1.2

Revision Date:  
31.12.2024

Date of last issue: 31.10.2024  
Date of first issue: 15.12.2022

---

skin. Repeated or prolonged contact with the mixture may cause removal of natural fat from the skin, resulting in non-allergic contact dermatitis and absorption through the skin. If splashed in the eyes, the liquid may cause irritation and reversible damage. This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact.

Risks : Causes skin irritation.  
May cause an allergic skin reaction.  
Causes serious eye irritation.

### 4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Treat symptomatically.

---

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media

Unsuitable extinguishing media : High volume water jet

### 5.2 Special hazards arising from the substance or mixture

Specific hazards during fire fighting : Do not allow run-off from fire fighting to enter drains or water courses.

### 5.3 Advice for firefighters

Special protective equipment for fire-fighters : Wear self-contained breathing apparatus for firefighting if necessary.

Further information : Collect contaminated fire extinguishing water separately. This must not be discharged into drains.  
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

---

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Use personal protective equipment.

### 6.2 Environmental precautions

Environmental precautions : Prevent product from entering drains.  
Prevent further leakage or spillage if safe to do so.  
If the product contaminates rivers and lakes or drains inform respective authorities.

---

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended

## Elastomastic™ TFN Comp. A

Version  
1.2

Revision Date:  
31.12.2024

Date of last issue: 31.10.2024  
Date of first issue: 15.12.2022

---

### 6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).  
Keep in suitable, closed containers for disposal.

### 6.4 Reference to other sections

See sections: 7, 8, 11, 12 and 13.

---

## SECTION 7: Handling and storage

### 7.1 Precautions for safe handling

Advice on safe handling : Good housekeeping standards, regular safe removal of waste materials and regular maintenance of spray booth filters will minimise the risks of spontaneous combustion and other fire hazards.

Do not breathe vapors/dust.  
Avoid exposure - obtain special instructions before use.  
Avoid contact with skin and eyes.  
For personal protection see section 8.  
Smoking, eating and drinking should be prohibited in the application area.  
To avoid spills during handling keep bottle on a metal tray.  
Dispose of rinse water in accordance with local and national regulations.  
Persons susceptible to skin sensitization problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.

Advice on protection against fire and explosion : Normal measures for preventive fire protection.

Hygiene measures : When using do not eat or drink. When using do not smoke.  
Wash hands before breaks and at the end of workday.

### 7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers : Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully re-sealed and kept upright to prevent leakage. Electrical installations / working materials must comply with the technological safety standards.

Storage class (TRGS 510) : 10

Further information on storage stability : No decomposition if stored and applied as directed.

### 7.3 Specific end use(s)

Specific use(s) : No data available

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended

## Elastomastic™ TFN Comp. A

Version  
1.2

Revision Date:  
31.12.2024

Date of last issue: 31.10.2024  
Date of first issue: 15.12.2022

### SECTION 8: Exposure controls/personal protection

#### 8.1 Control parameters

##### Occupational Exposure Limits

Contains no substances with occupational exposure limit values.

#### 8.2 Exposure controls

##### Personal protective equipment

- |                          |   |   |
|--------------------------|---|---|
| Eye/face protection      | : | Eye wash bottle with pure water<br>Safety glasses with side-shields conforming to EN166<br><br>Tightly fitting safety goggles<br>Wear face-shield and protective suit for abnormal processing problems.   |
| Hand protection          |   |   |
| Material                 | : | Chemical resistant gloves made of butyl rubber or nitrile rubber category III according to EN 374.  |
| Glove length             | : | Standard glove type.  |
| Guideline                | : | Equipment should conform to EN 374  |
| Material                 | : | Protective equipment only chosen according to specific regulatory requirements after a risk assessment.   |
| Remarks                  | : | Follow the instructions for use issued by the producer.<br>Gloves should be discarded and replaced if there is any indication of degradation or chemical breakthrough. Be aware that in daily use the durability of a chemical resistant protective glove can be notably shorter than the break through time measured according to EN 374, due to the numerous outside influences (e.g. temperature). The choice of an appropriate glove does not only depend on its material but also on other quality features and is different from one producer to the other. Barrier creams may help to protect the exposed areas of skin, they should however not be applied once exposure has occurred.<br>The suitability for a specific workplace should be discussed with the producers of the protective gloves. |
| Skin and body protection | : | Protective equipment only chosen according to specific regulatory requirements after a risk assessment.<br>Equipment should conform to EN 14605<br><br>Impervious clothing<br>Choose body protection according to the amount and concentration of the dangerous substance at the work place.  |
| Respiratory protection   | : | Equipment should conform to EN 14387  |

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended

## Elastomastic™ TFN Comp. A

Version  
1.2

Revision Date:  
31.12.2024

Date of last issue: 31.10.2024  
Date of first issue: 15.12.2022

General and local exhaust ventilation is recommended to maintain vapor exposures below recommended limits. Where concentrations are above recommended limits or are unknown, appropriate respiratory protection should be worn. Follow OSHA respirator regulations (29 CFR 1910.134) and use NIOSH/MSHA approved respirators. Protection provided by air purifying respirators against exposure to any hazardous chemical is limited. Use a positive pressure air supplied respirator if there is any potential for uncontrolled release, exposure levels are unknown, or any other circumstance where air purifying respirators may not provide adequate protection. When workers are facing concentrations above the exposure limit they must use appropriate certified respirators.

No personal respiratory protective equipment normally required.

Filter type : Combined particulates and organic vapor type (A-P)

Protective measures : In case of insufficient ventilation, wear suitable respiratory equipment.

### Environmental exposure controls

Water : The product should not be allowed to enter drains, water courses or the soil.

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

Physical state : liquid

Color : black

Odor : slight

Odor Threshold : No data available

Upper explosion limit / Upper flammability limit : No data available

Lower explosion limit / Lower flammability limit : No data available

Flash point : > 101 °C  
Method: closed cup



# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended

## Elastomastic™ TFN Comp. A

Version  
1.2

Revision Date:  
31.12.2024

Date of last issue: 31.10.2024  
Date of first issue: 15.12.2022

---

Decomposition temperature	:	Not relevant/applicable due to the nature of the product.
pH	:	Not applicable substance/mixture is non-soluble (in water)
Viscosity		
Viscosity, dynamic	:	ca. 20.000 mPa.s (20 °C)
Viscosity, kinematic	:	> 20,5 mm <sup>2</sup> /s (40 °C)
Solubility(ies)		
Water solubility	:	insoluble
Partition coefficient: n-octanol/water	:	Not relevant/applicable due to the nature of the product.
Vapor pressure	:	0,01 hPa
Density	:	ca. 1,10 g/cm <sup>3</sup> (20 °C)
Relative vapor density	:	No data available

### 9.2 Other information

Explosives	:	No dangerous reaction known under conditions of normal use.
Oxidizing properties	:	No dangerous reaction known under conditions of normal use.
Self-ignition	:	Not relevant/applicable due to the nature of the product.

---

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

No hazards to be specially mentioned.  
No decomposition if stored and applied as directed.

### 10.2 Chemical stability

Stable under normal conditions.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended

## Elastomastic™ TFN Comp. A

Version  
1.2

Revision Date:  
31.12.2024

Date of last issue: 31.10.2024  
Date of first issue: 15.12.2022

No decomposition if stored and applied as directed.

### 10.3 Possibility of hazardous reactions

Hazardous reactions : No dangerous reaction known under conditions of normal use.  
No decomposition if stored and applied as directed.

### 10.4 Conditions to avoid

Conditions to avoid : Temperatures greater than recommended storage temperature.

### 10.5 Incompatible materials

Materials to avoid : Strong acids and strong bases  
Strong oxidizing agents

### 10.6 Hazardous decomposition products

Carbon dioxide (CO<sub>2</sub>), carbon monoxide (CO), oxides of nitrogen (NO<sub>x</sub>), dense black smoke.

## SECTION 11: Toxicological information

### 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Information on likely routes of exposure : There are no data available on the mixture itself. Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS] See Sections 2 and 3 for details. Exposure to component solvent vapour concentrations in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and, in extreme cases, loss of consciousness. Solvents may cause some of the above effects by absorption through the skin. Repeated or prolonged contact with the mixture may cause removal of natural fat from the skin, resulting in non-allergic contact dermatitis and absorption through the skin. If splashed in the eyes, the liquid may cause irritation and reversible damage. This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact.

#### Acute toxicity

Not classified due to lack of data.

#### Product:

Acute oral toxicity : Acute toxicity estimate: > 2.000 mg/kg  
Method: Calculation method

Acute dermal toxicity : Acute toxicity estimate: > 2.000 mg/kg  
Method: Calculation method

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended

## Elastomastic™ TFN Comp. A

Version  
1.2

Revision Date:  
31.12.2024

Date of last issue: 31.10.2024  
Date of first issue: 15.12.2022

---

### **Components:**

#### **bis-[4-(2,3-epoxipropoxy)phenyl]propane:**

Acute oral toxicity : LD50 Oral (Rat): > 5.000 mg/kg

Acute dermal toxicity : LD50 Dermal (Rabbit): > 5.000 mg/kg

#### **Cashew, nutshell liq.:**

Acute oral toxicity : LD50 Oral (Rat): 500 mg/kg

Acute dermal toxicity : LD50 Dermal (Rat): 2.000 mg/kg

#### **reaction product: bisphenol-A(epichlorhydrin); epoxy resin (number average molecular weight ≤ 700):**

Acute oral toxicity : LD50 Oral (Rat): > 5.000 mg/kg

Acute dermal toxicity : LD50 Dermal (Rabbit): > 20.000 mg/kg

#### **oxirane, mono[(C12-14-alkyloxy)methyl] derivs.:**

Acute oral toxicity : LD50 Oral (Rat): > 5.000 mg/kg

### **Skin corrosion/irritation**

Causes skin irritation.

### **Product:**

Remarks : Extremely corrosive and destructive to tissue.

### **Serious eye damage/eye irritation**

Causes serious eye irritation.

### **Product:**

Remarks : May cause irreversible eye damage.

### **Respiratory or skin sensitization**

#### **Skin sensitization**

May cause an allergic skin reaction.

#### **Respiratory sensitization**

Not classified due to lack of data.

### **Product:**

Remarks : Causes sensitization.

### **Germ cell mutagenicity**

Not classified due to lack of data.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended

## Elastomastic™ TFN Comp. A

Version  
1.2

Revision Date:  
31.12.2024

Date of last issue: 31.10.2024  
Date of first issue: 15.12.2022

---

### Carcinogenicity

Not classified due to lack of data.

### Reproductive toxicity

Not classified due to lack of data.

### STOT-single exposure

Not classified due to lack of data.

### STOT-repeated exposure

Not classified due to lack of data.

### Aspiration toxicity

Not classified due to lack of data.

## 11.2 Information on other hazards

### Endocrine disrupting properties

#### Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

### Further information

#### Product:

Remarks : No data available

---

## SECTION 12: Ecological information

### 12.1 Toxicity

#### Components:

##### **bis-[4-(2,3-epoxipropoxy)phenyl]propane:**

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 2 mg/l  
Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 1,8 mg/l  
Exposure time: 48 h

##### **reaction product: bisphenol-A(epichlorhydrin); epoxy resin (number average molecular weight ≤ 700):**

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 2 mg/l  
Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 1,8 mg/l  
Exposure time: 48 h

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended

## Elastomastic™ TFN Comp. A

Version  
1.2

Revision Date:  
31.12.2024

Date of last issue: 31.10.2024  
Date of first issue: 15.12.2022

---

### 12.2 Persistence and degradability

No data available

### 12.3 Bioaccumulative potential

No data available

### 12.4 Mobility in soil

No data available

### 12.5 Results of PBT and vPvB assessment

#### Product:

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

### 12.6 Endocrine disrupting properties

#### Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

### 12.7 Other adverse effects

#### Product:

Additional ecological information : The product should not be allowed to enter drains, water courses or the soil.

An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.  
Toxic to aquatic life with long lasting effects.

---

## SECTION 13: Disposal considerations

### 13.1 Waste treatment methods

Product : The product should not be allowed to enter drains, water courses or the soil.  
Do not contaminate ponds, waterways or ditches with chemical or used container.  
Send to a licensed waste management company.

Contaminated packaging : Empty remaining contents.  
Dispose of as unused product.  
Do not re-use empty containers.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended

## Elastomastic™ TFN Comp. A

Version  
1.2

Revision Date:  
31.12.2024

Date of last issue: 31.10.2024  
Date of first issue: 15.12.2022

### SECTION 14: Transport information

#### 14.1 UN number or ID number

**ADR** : UN 3082  
**IMDG** : UN 3082  
**IATA** : UN 3082

#### 14.2 UN proper shipping name

**ADR** : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.  
(bis-[4-(2,3-epoxipropoxi)phenyl]propane)  
**IMDG** : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.  
(bis-[4-(2,3-epoxipropoxi)phenyl]propane)  
**IATA** : Environmentally hazardous substance, liquid, n.o.s.  
(bis-[4-(2,3-epoxipropoxi)phenyl]propane)

#### 14.3 Transport hazard class(es)

	Class	Subsidiary risks
<b>ADR</b>	: 9	
<b>IMDG</b>	: 9	
<b>IATA</b>	: 9	

#### 14.4 Packing group

**ADR**  
Packing group : III  
Classification Code : M6  
Hazard Identification Number : 90  
Labels : 9  
Tunnel restriction code : (-)

**IMDG**  
Packing group : III  
Labels : 9  
EmS Code : F-A, S-F

**IATA (Cargo)**  
Packing instruction (cargo aircraft) : 964  
Packing instruction (LQ) : Y964  
Packing group : III  
Labels : Miscellaneous

**IATA (Passenger)**  
Packing instruction (passenger aircraft) : 964  
Packing instruction (LQ) : Y964

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended

## Elastomastic™ TFN Comp. A

Version	Revision Date:	Date of last issue: 31.10.2024
1.2	31.12.2024	Date of first issue: 15.12.2022

Packing group : III  
Labels : Miscellaneous

### 14.5 Environmental hazards

#### ADR

Environmentally hazardous : yes

#### IMDG

Marine pollutant : yes

### 14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

### 14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

## SECTION 15: Regulatory information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII) : Conditions of restriction for the following entries should be considered:  
Number on list 3

REACH - Candidate List of Substances of Very High Concern for Authorization (Article 59). : Number on list 75:  
Not applicable

Regulation (EU) No 2024/590 on substances that deplete the ozone layer : Not applicable

Regulation (EU) 2019/1021 on persistent organic pollutants (recast) : Not applicable

Regulation (EU) No 649/2012 of the European Parliament and the Council concerning the export and import of dangerous chemicals : Not applicable

REACH - List of substances subject to authorisation (Annex XIV) : Not applicable

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances. E2 ENVIRONMENTAL HAZARDS

Water hazard class (Germa- : WGK 2 obviously hazardous to water

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended

## Elastomastic™ TFN Comp. A

Version  
1.2

Revision Date:  
31.12.2024

Date of last issue: 31.10.2024  
Date of first issue: 15.12.2022

ny) Classification according to AwSV, Annex 1 (5.2)

TA Luft List (Germany) : 5.2.7.1.3: Substances toxic to reproduction:  
others: 0,1 % 68609-97-2, 70657-70-4

Volatile organic compounds : Directive 2010/75/EU of 24 November 2010 on industrial and  
livestock rearing emissions (integrated pollution prevention  
and control)  
Volatile organic compounds (VOC) content: 0,65 %

### Other regulations:

Take note of Law on the protection of mothers at work, in education and in studies (Maternity  
Protection Act - MuSchG).

Take note of Directive 94/33/EC on the protection of young people at work or stricter national  
regulations, where applicable.

### 15.2 Chemical Safety Assessment

No Chemical Safety Assessment has been carried out for this mixture.

This product is in full compliance according to REACH regulation 1907/2006/EC.

## SECTION 16: Other information

### Full text of H-Statements

H302 : Harmful if swallowed.  
H312 : Harmful in contact with skin.  
H315 : Causes skin irritation.  
H317 : May cause an allergic skin reaction.  
H318 : Causes serious eye damage.  
H319 : Causes serious eye irritation.  
H360F : May damage fertility.  
H411 : Toxic to aquatic life with long lasting effects.  
H412 : Harmful to aquatic life with long lasting effects.

### Full text of other abbreviations

Acute Tox. : Acute toxicity  
Aquatic Chronic : Long-term (chronic) aquatic hazard  
Eye Dam. : Serious eye damage  
Eye Irrit. : Eye irritation  
Repr. : Reproductive toxicity  
Skin Irrit. : Skin irritation  
Skin Sens. : Skin sensitization

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland  
Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by  
Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Test-  
ing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regula-  
tion (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard  
of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA -



# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended

## Elastomastic™ TFN Comp. A

Version 1.2  
Revision Date: 31.12.2024

Date of last issue: 31.10.2024  
Date of first issue: 15.12.2022

European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - substance of very high concern; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

### Further information

#### Classification of the mixture:

Skin Irrit. 2	H315
Eye Irrit. 2	H319
Skin Sens. 1	H317
Aquatic Chronic 2	H411

#### Classification procedure:

Calculation method
Calculation method
Calculation method
Calculation method

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

It is recommended that each customer or recipient of this Safety Data Sheet (SDS) study it carefully and consult resources, as necessary or appropriate, to become aware of and understand the data contained in this SDS and any hazards associated with the product. This information is provided in good faith and believed to be accurate as of the effective date herein. However, no warranty, express or implied, is given. The information presented here applies only to the product as shipped. The addition of any material can change the composition, hazards and risks of the product. Products shall not be repackaged, modified, or tinted except as specifically instructed by the manufacturer, including but not limited to the incorporation of products not specified by the manufacturer, or the use or addition of products in proportions not specified by the manufacturer. Regulatory requirements are subject to change and may differ between various locations and jurisdictions. The customer/buyer/user is re-

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended

## Elastomastic™ TFN Comp. A

Version  
1.2

Revision Date:  
31.12.2024

Date of last issue: 31.10.2024  
Date of first issue: 15.12.2022

---

sponsible to ensure that his activities comply with all country, federal, state, provincial or local laws. The conditions for use of the product are not under the control of the manufacturer; the customer/buyer/user is responsible to determine the conditions necessary for the safe use of this product. The customer/buyer/user should not use the product for any purpose other than the purpose shown in the applicable section of this SDS without first referring to the supplier and obtaining written handling instructions. Due to the proliferation of sources for information such as manufacturer-specific SDS, the manufacturer cannot be responsible for SDSs obtained from any other source.

DE / EN