

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended

## Magnalux™ VE Hardener Comp. B

Version  
1.3

Revision Date:  
10.01.2025

Date of last issue: 01.12.2023  
Date of first issue: 14.12.2022

---

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

Trade name : Magnalux™ VE Hardener Comp. B  
Product code : 000000000000449131

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Sub-stance/Mixture : Coatings and paints, thinners, paint removers  
Recommended restrictions on use : Reserved for industrial and professional use.

#### 1.3 Details of the supplier of the safety data sheet

Company : Sherwin-Williams Coatings  
Deutschland GmbH  
Rieter Tal 1  
71665 Vaihingen / Enz  
Telephone : +4970421090  
E-mail address of person responsible for the SDS : SDS-DE@sherwin.com

#### 1.4 Emergency telephone

##### National advisory body/Poison Center

Telephone number: Not available

##### Supplier

Telephone number: +49 (0) 7042 109-0

Hours of operation: Emergency contact available 24 hours a day

---

### SECTION 2: Hazards identification

#### 2.1 Classification of the substance or mixture

##### Classification (REGULATION (EC) No 1272/2008)

Organic peroxides, Type F	H242: Heating may cause a fire.
Acute toxicity, Category 4	H302: Harmful if swallowed.
Acute toxicity, Category 3	H331: Toxic if inhaled.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended

## Magnalux™ VE Hardener Comp. B

Version  
1.3

Revision Date:  
10.01.2025

Date of last issue: 01.12.2023  
Date of first issue: 14.12.2022

Acute toxicity, Category 4	H312: Harmful in contact with skin.
Skin corrosion, Sub-category 1B	H314: Causes severe skin burns and eye damage.
Serious eye damage, Category 1	H318: Causes serious eye damage.
Carcinogenicity, Category 1B	H350: May cause cancer.
Reproductive toxicity, Category 1B	H360D: May damage the unborn child.
Specific target organ toxicity - single exposure, Category 3, Respiratory system	H335: May cause respiratory irritation.
Specific target organ toxicity - repeated exposure, Category 2	H373: May cause damage to organs through prolonged or repeated exposure.
Long-term (chronic) aquatic hazard, Category 2	H411: Toxic to aquatic life with long lasting effects.

### 2.2 Label elements

#### Labeling (REGULATION (EC) No 1272/2008)

Hazard pictograms :



Signal Word : Danger

Hazard Statements :

H242	Heating may cause a fire.
H302 + H312	Harmful if swallowed or in contact with skin.
H314	Causes severe skin burns and eye damage.
H331	Toxic if inhaled.
H335	May cause respiratory irritation.
H350	May cause cancer.
H360D	May damage the unborn child.
H373	May cause damage to organs through prolonged or repeated exposure.
H411	Toxic to aquatic life with long lasting effects.

Precautionary Statements : **Prevention:**

P201	Obtain special instructions before use.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P234	Keep only in original packaging.
P260	Do not breathe mist or vapors.
P273	Avoid release to the environment.
P280	Wear protective gloves/ protective clothing/ eye protection/ face protection/ hearing protection.

#### **Response:**

P303 + P361 + P353 IF ON SKIN (or hair): Take off immedi-

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended

## Magnalux™ VE Hardener Comp. B

Version  
1.3

Revision Date:  
10.01.2025

Date of last issue: 01.12.2023  
Date of first issue: 14.12.2022

ately all contaminated clothing. Rinse skin with water.

P304 + P340 + P310 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Immediately call a POISON CENTER/ doctor.

P305 + P351 + P338 + P310 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/ doctor.

P308 + P313 IF exposed or concerned: Get medical advice/ attention.

P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

P391 Collect spillage.

### Storage:

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.

### Hazardous ingredients which must be listed on the label:

$\alpha$ ,  $\alpha$ -dimethylbenzyl hydroperoxide  
2-phenylpropan-2-ol  
cumene  
bis( $\alpha$ , $\alpha$ -dimethylbenzyl) peroxide

### Additional Labeling

Restricted to professional users.

## 2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

## SECTION 3: Composition/information on ingredients

### 3.2 Mixtures

#### Components

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	Concentration (% w/w)
$\alpha$ , $\alpha$ -dimethylbenzyl hydroperox-	80-15-9	Org. Perox. E; H242	>= 70 - < 90

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended

## Magnalux™ VE Hardener Comp. B

Version  
1.3

Revision Date:  
10.01.2025

Date of last issue: 01.12.2023  
Date of first issue: 14.12.2022

ide	201-254-7 617-002-00-8	Acute Tox. 4; H302 Acute Tox. 3; H331 Acute Tox. 4; H312 Skin Corr. 1B; H314 STOT RE 2; H373 STOT RE 2; H373 Aquatic Chronic 2; H411  specific concentration limit Skin Corr. 1B; H314 ≥ 10 % Skin Irrit. 2; H315 3 - < 10 % Eye Dam. 1; H318 3 - < 10 % Eye Irrit. 2; H319 1 - < 3 % STOT SE 3; H335 ≥ 1 %	
2-phenylpropan-2-ol	617-94-7 210-539-5	Acute Tox. 4; H302 Skin Irrit. 2; H315 Eye Irrit. 2; H319	≥ 1 - < 10
cumene	98-82-8 202-704-5 601-024-00-X	Flam. Liq. 3; H226 Asp. Tox. 1; H304 STOT SE 3; H335 Aquatic Chronic 2; H411 Carc. 1B; H350	≥ 1 - < 2,5
acetophenone	98-86-2 202-708-7 606-042-00-1	Acute Tox. 4; H302 Eye Irrit. 2; H319	≥ 1 - < 10
bis(α,α-dimethylbenzyl) peroxide	80-43-3 201-279-3 617-006-00-X 01-2119541688-27	2; H315 5.2 F; H242 2; H319 Repr. 1B; H360D Aquatic Chronic 2; H411	≥ 0,3 - < 1

For explanation of abbreviations see section 16.

## SECTION 4: First aid measures

### 4.1 Description of first-aid measures

General advice : Move out of dangerous area.  
Consult a physician.  
Show this material safety data sheet to the doctor in attendance.  
Symptoms of poisoning may appear several hours later.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended

## Magnalux™ VE Hardener Comp. B

Version  
1.3

Revision Date:  
10.01.2025

Date of last issue: 01.12.2023  
Date of first issue: 14.12.2022

---

Do not leave the victim unattended.

- If inhaled : Call a physician or poison control center immediately.  
If unconscious, place in recovery position and seek medical advice.
- In case of skin contact : Immediate medical treatment is necessary as untreated wounds from corrosion of the skin heal slowly and with difficulty.  
If on skin, rinse well with water.  
If on clothes, remove clothes.
- In case of eye contact : Small amounts splashed into eyes can cause irreversible tissue damage and blindness.  
In the case of contact with eyes, rinse immediately with plenty of water and seek medical advice.  
Continue rinsing eyes during transport to hospital.  
Remove contact lenses.  
Protect unharmed eye.  
Keep eye wide open while rinsing.  
If eye irritation persists, consult a specialist.
- If swallowed : Clean mouth with water and drink afterwards plenty of water.  
Keep respiratory tract clear.  
Do NOT induce vomiting.  
Do not give milk or alcoholic beverages.  
Never give anything by mouth to an unconscious person.  
If symptoms persist, call a physician.  
Take victim immediately to hospital.

### 4.2 Most important symptoms and effects, both acute and delayed

- Symptoms : There are no data available on the mixture itself. Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS] See Sections 2 and 3 for details.  
Exposure to component solvent vapour concentrations in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and, in extreme cases, loss of consciousness. Solvents may cause some of the above effects by absorption through the skin. Repeated or prolonged contact with the mixture may cause removal of natural fat from the skin, resulting in non-allergic contact dermatitis and absorption through the skin. If splashed in the eyes, the liquid may cause irritation and reversible damage. This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact.
- Risks : Harmful if swallowed or in contact with skin.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended

## Magnalux™ VE Hardener Comp. B

Version  
1.3

Revision Date:  
10.01.2025

Date of last issue: 01.12.2023  
Date of first issue: 14.12.2022

Causes serious eye damage.  
Toxic if inhaled.  
May cause respiratory irritation.  
May cause cancer.  
May damage the unborn child.  
May cause damage to organs through prolonged or repeated exposure.  
Causes severe burns.

### 4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Treat symptomatically.

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media

Suitable extinguishing media : Alcohol-resistant foam  
Carbon dioxide (CO<sub>2</sub>)  
Dry chemical

Unsuitable extinguishing media : High volume water jet

### 5.2 Special hazards arising from the substance or mixture

Specific hazards during fire fighting : Do not allow run-off from fire fighting to enter drains or water courses.

### 5.3 Advice for firefighters

Special protective equipment for fire-fighters : Wear self-contained breathing apparatus for firefighting if necessary.

Further information : Collect contaminated fire extinguishing water separately. This must not be discharged into drains.  
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.  
For safety reasons in case of fire, cans should be stored separately in closed containments.  
Use a water spray to cool fully closed containers.

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Use personal protective equipment.  
Ensure adequate ventilation.  
Remove all sources of ignition.  
Evacuate personnel to safe areas.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended

## Magnalux™ VE Hardener Comp. B

Version  
1.3

Revision Date:  
10.01.2025

Date of last issue: 01.12.2023  
Date of first issue: 14.12.2022

---

### 6.2 Environmental precautions

Environmental precautions : Prevent product from entering drains.  
Prevent further leakage or spillage if safe to do so.  
If the product contaminates rivers and lakes or drains inform respective authorities.

### 6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

### 6.4 Reference to other sections

See sections: 7, 8, 11, 12 and 13.

---

## SECTION 7: Handling and storage

### 7.1 Precautions for safe handling

Advice on safe handling : Good housekeeping standards, regular safe removal of waste materials and regular maintenance of spray booth filters will minimise the risks of spontaneous combustion and other fire hazards.

Avoid formation of aerosol.  
Do not breathe vapors/dust.  
Avoid exposure - obtain special instructions before use.  
Avoid contact with skin and eyes.  
For personal protection see section 8.  
Smoking, eating and drinking should be prohibited in the application area.  
Provide sufficient air exchange and/or exhaust in work rooms.  
Open drum carefully as content may be under pressure.  
To avoid spills during handling keep bottle on a metal tray.  
Dispose of rinse water in accordance with local and national regulations.

Advice on protection against fire and explosion : Keep away from open flames, hot surfaces and sources of ignition.

Hygiene measures : Avoid contact with skin, eyes and clothing. When using do not eat or drink. When using do not smoke. Wash hands before breaks and immediately after handling the product.

### 7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers : Prevent unauthorized access. Store in cool place. Keep in a well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Observe label precautions. Electrical installations / working materials must comply with the technological safety standards.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended

## Magnalux™ VE Hardener Comp. B

Version  
1.3

Revision Date:  
10.01.2025

Date of last issue: 01.12.2023  
Date of first issue: 14.12.2022

Storage class (TRGS 510) : 5.2

Further information on storage stability : No decomposition if stored and applied as directed.

### 7.3 Specific end use(s)

Specific use(s) : No data available

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

#### Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
cumene	98-82-8	TWA	20 ppm 100 mg/m <sup>3</sup>	2000/39/EC
	Further information: Identifies the possibility of significant uptake through the skin, Indicative			
		STEL	50 ppm 250 mg/m <sup>3</sup>	2000/39/EC
	Further information: Identifies the possibility of significant uptake through the skin, Indicative			
		TWA	10 ppm 50 mg/m <sup>3</sup>	2019/1831/EU
	Further information: A skin notation assigned to the occupational exposure limit value indicates the possibility of significant uptake through the skin., Indicative			
		STEL	50 ppm 250 mg/m <sup>3</sup>	2019/1831/EU
	Further information: A skin notation assigned to the occupational exposure limit value indicates the possibility of significant uptake through the skin., Indicative			
		AGW	10 ppm 50 mg/m <sup>3</sup>	DE TRGS 900
	Peak-limit category: 4;(II)			
	Further information: Carcinogenic substance Cat. 1A or 1B or carcinogenic activity or procedure according to § 2 (3) No. 4 of the Hazardous Substances Ordinance - in addition, § 10 GefStoffV must be observed, Skin absorption, When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child			
		MAK	10 ppm 50 mg/m <sup>3</sup>	DE DFG MAK
	Peak-limit category: 4; II			
	Further information: Substances that cause concern that they could be carcinogenic for man but cannot be assessed conclusively because of lack of data, Danger of absorption through the skin, Damage to the embryo or foetus is unlikely when the MAK value or the BAT value is observed			



# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended

## Magnalux™ VE Hardener Comp. B

Version  
1.3

Revision Date:  
10.01.2025

Date of last issue: 01.12.2023  
Date of first issue: 14.12.2022

### Biological occupational exposure limits

Substance name	CAS-No.	Control parameters	Sampling time	Basis
cumene	98-82-8	2-phenyl-2-propanol: 10 mg/g creatinine (Urine)	Immediately after exposure or after working hours	TRGS 903
		iso-propylbenzene: 10 mg/g creatinine (Urine)	Immediately after exposition or after working hours	DE DFG BAT

### 8.2 Exposure controls

#### Personal protective equipment

Eye/face protection : Eye wash bottle with pure water  
Safety glasses with side-shields conforming to EN166  
  
Tightly fitting safety goggles  
Wear face-shield and protective suit for abnormal processing problems.

#### Hand protection

Material : Chemical resistant gloves made of butyl rubber or nitrile rubber category III according to EN 374.  
Glove length : Standard glove type.  
Guideline : Equipment should conform to EN 374  
  
Material : Protective equipment only chosen according to specific regulatory requirements after a risk assessment.

#### Remarks

: Follow the instructions for use issued by the producer.  
Gloves should be discarded and replaced if there is any indication of degradation or chemical breakthrough. Be aware that in daily use the durability of a chemical resistant protective glove can be notably shorter than the break through time measured according to EN 374, due to the numerous outside influences (e.g. temperature). The choice of an appropriate glove does not only depend on its material but also on other quality features and is different from one producer to the other. Barrier creams may help to protect the exposed areas of skin, they should however not be applied once exposure has occurred.  
The suitability for a specific workplace should be discussed with the producers of the protective gloves.

#### Skin and body protection

: Protective equipment only chosen according to specific regulatory requirements after a risk assessment.  
Equipment should conform to EN 14605  
  
Impervious clothing  
Choose body protection according to the amount and concentration of the dangerous substance at the work place.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended

## Magnalux™ VE Hardener Comp. B

Version  
1.3

Revision Date:  
10.01.2025

Date of last issue: 01.12.2023  
Date of first issue: 14.12.2022

Respiratory protection : Equipment should conform to EN 14387  
General and local exhaust ventilation is recommended to maintain vapor exposures below recommended limits. Where concentrations are above recommended limits or are unknown, appropriate respiratory protection should be worn. Follow OSHA respirator regulations (29 CFR 1910.134) and use NIOSH/MSHA approved respirators. Protection provided by air purifying respirators against exposure to any hazardous chemical is limited. Use a positive pressure air supplied respirator if there is any potential for uncontrolled release, exposure levels are unknown, or any other circumstance where air purifying respirators may not provide adequate protection. When workers are facing concentrations above the exposure limit they must use appropriate certified respirators.

No personal respiratory protective equipment normally required.

Filter type : Combined particulates and organic vapor type (A-P)

Protective measures : In case of insufficient ventilation, wear suitable respiratory equipment.

### Environmental exposure controls

Water : The product should not be allowed to enter drains, water courses or the soil.

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

Physical state : liquid

Color : colorless

Odor : pungent

Odor Threshold : No data available

Melting point/freezing point : ca. -30 °C

Boiling point/boiling range : 100 °C  
Decomposition at boiling point.

Upper explosion limit / Upper flammability limit : No data available

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended

## Magnalux™ VE Hardener Comp. B

Version  
1.3

Revision Date:  
10.01.2025

Date of last issue: 01.12.2023  
Date of first issue: 14.12.2022

---

Lower explosion limit / Lower flammability limit : No data available

Flash point : > 101 °C  
Method: closed cup  
Decomposition

Decomposition temperature : Not relevant/applicable due to the nature of the product.

Self-Accelerating decomposition temperature (SADT) : 70 °C

pH : ca. 6,0 (20 °C)  
Concentration: 100 %

Viscosity  
Viscosity, dynamic : 10,9 mPa.s (20 °C)

Viscosity, kinematic : < 20,5 mm<sup>2</sup>/s (40 °C)

Solubility(ies)  
Water solubility : soluble

Partition coefficient: n-octanol/water : Not relevant/applicable due to the nature of the product.

Vapor pressure : 13,33 hPa

Density : 1,06 g/cm<sup>3</sup> (20 °C)

Relative vapor density : No data available

### 9.2 Other information

Explosives : No dangerous reaction known under conditions of normal use.  
Not relevant/applicable due to the nature of the product.

Oxidizing properties : No dangerous reaction known under conditions of normal use.  
Not relevant/applicable due to the nature of the product.

Self-ignition : Not relevant/applicable due to the nature of the product.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended

## Magnalux™ VE Hardener Comp. B

Version  
1.3

Revision Date:  
10.01.2025

Date of last issue: 01.12.2023  
Date of first issue: 14.12.2022

---

### SECTION 10: Stability and reactivity

#### 10.1 Reactivity

No hazards to be specially mentioned.  
No decomposition if stored and applied as directed.

#### 10.2 Chemical stability

Stable under normal conditions.  
No decomposition if stored and applied as directed.

#### 10.3 Possibility of hazardous reactions

Hazardous reactions : No dangerous reaction known under conditions of normal use.  
No decomposition if stored and applied as directed.

#### 10.4 Conditions to avoid

Conditions to avoid : Temperatures greater than recommended storage temperature.  
Heat, flames and sparks.

#### 10.5 Incompatible materials

Materials to avoid : Strong acids and strong bases  
Strong oxidizing agents

#### 10.6 Hazardous decomposition products

Carbon dioxide (CO<sub>2</sub>), carbon monoxide (CO), oxides of nitrogen (NO<sub>x</sub>), dense black smoke.

---

### SECTION 11: Toxicological information

#### 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Information on likely routes of exposure : There are no data available on the mixture itself. Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS] See Sections 2 and 3 for details. Exposure to component solvent vapour concentrations in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and, in extreme cases, loss of consciousness. Solvents may cause some of the above effects by absorption through the skin. Repeated or prolonged contact with the mixture may cause removal of natural fat from the skin, resulting in non-allergic contact dermatitis and absorption through the skin. If splashed in the eyes, the liquid may cause irritation and re-

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended

## Magnalux™ VE Hardener Comp. B

Version  
1.3

Revision Date:  
10.01.2025

Date of last issue: 01.12.2023  
Date of first issue: 14.12.2022

---

versible damage. This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact.

### Acute toxicity

Harmful if swallowed or in contact with skin.  
Toxic if inhaled.

#### Product:

Acute oral toxicity	:	Acute toxicity estimate: 513,29 mg/kg Method: Calculation method
Acute inhalation toxicity	:	Acute toxicity estimate: 3,45 mg/l Exposure time: 4 h Test atmosphere: vapor Method: Calculation method
Acute dermal toxicity	:	Acute toxicity estimate: 1.265 mg/kg Method: Calculation method

### Skin corrosion/irritation

Causes severe burns.

#### Product:

Remarks : Extremely corrosive and destructive to tissue.

### Serious eye damage/eye irritation

Causes serious eye damage.

#### Product:

Remarks : May cause irreversible eye damage.

### Respiratory or skin sensitization

#### Skin sensitization

Not classified due to lack of data.

#### Respiratory sensitization

Not classified due to lack of data.

#### Germ cell mutagenicity

Not classified due to lack of data.

#### Carcinogenicity

May cause cancer.

#### Reproductive toxicity

May damage the unborn child.

#### STOT-single exposure

May cause respiratory irritation.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended

## Magnalux™ VE Hardener Comp. B

Version  
1.3

Revision Date:  
10.01.2025

Date of last issue: 01.12.2023  
Date of first issue: 14.12.2022

---

### STOT-repeated exposure

May cause damage to organs through prolonged or repeated exposure.

### Aspiration toxicity

Not classified due to lack of data.

## 11.2 Information on other hazards

### Endocrine disrupting properties

#### Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

### Further information

#### Product:

Remarks : No data available

---

## SECTION 12: Ecological information

### 12.1 Toxicity

No data available

### 12.2 Persistence and degradability

No data available

### 12.3 Bioaccumulative potential

No data available

### 12.4 Mobility in soil

No data available

### 12.5 Results of PBT and vPvB assessment

#### Product:

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

### 12.6 Endocrine disrupting properties

#### Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended

## Magnalux™ VE Hardener Comp. B

Version  
1.3

Revision Date:  
10.01.2025

Date of last issue: 01.12.2023  
Date of first issue: 14.12.2022

### 12.7 Other adverse effects

#### Product:

Additional ecological information : The product should not be allowed to enter drains, water courses or the soil.

An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.  
Toxic to aquatic life with long lasting effects.

## SECTION 13: Disposal considerations

### 13.1 Waste treatment methods

Product : The product should not be allowed to enter drains, water courses or the soil.  
Do not contaminate ponds, waterways or ditches with chemical or used container.  
Send to a licensed waste management company.

Contaminated packaging : Empty remaining contents.  
Dispose of as unused product.  
Do not re-use empty containers.  
Do not burn, or use a cutting torch on, the empty drum.

## SECTION 14: Transport information

### 14.1 UN number or ID number

ADR : UN 3109  
IMDG : UN 3109  
IATA : UN 3109

### 14.2 UN proper shipping name

ADR : ORGANIC PEROXIDE TYPE F, LIQUID  
( $\alpha,\alpha$ -dimethylbenzyl hydroperoxide)  
IMDG : ORGANIC PEROXIDE TYPE F, LIQUID  
( $\alpha,\alpha$ -dimethylbenzyl hydroperoxide)  
IATA : Organic peroxide type F, liquid (Cumyl hydroperoxide)  
( $\alpha,\alpha$ -dimethylbenzyl hydroperoxide)

### 14.3 Transport hazard class(es)

	Class	Subsidiary risks
ADR	: 5.2	

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended

## Magnalux™ VE Hardener Comp. B

Version  
1.3

Revision Date:  
10.01.2025

Date of last issue: 01.12.2023  
Date of first issue: 14.12.2022

**IMDG** : 5.2

**IATA** : 5.2 HEAT, 8

### 14.4 Packing group

#### ADR

Packing group : Not assigned by regulation  
Classification Code : P1  
Hazard Identification Number : 539  
Labels : 5.2  
Tunnel restriction code : (D)

#### IMDG

Packing group : Not assigned by regulation  
Labels : 5.2  
EmS Code : F-J, S-R

#### IATA (Cargo)

Packing instruction (cargo aircraft) : 570  
Packing group : Not assigned by regulation  
Labels : Organic Peroxides, Keep Away From Heat, Corrosive

#### IATA (Passenger)

Packing instruction (passenger aircraft) : 570  
Packing group : Not assigned by regulation  
Labels : Organic Peroxides, Keep Away From Heat, Corrosive

### 14.5 Environmental hazards

#### ADR

Environmentally hazardous : yes

#### IMDG

Marine pollutant : yes

### 14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

### 14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

## SECTION 15: Regulatory information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII) : Conditions of restriction for the following entries should be considered: Number on list 3



# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended

## Magnalux™ VE Hardener Comp. B

Version  
1.3

Revision Date:  
10.01.2025

Date of last issue: 01.12.2023  
Date of first issue: 14.12.2022

		Number on list 28: cumene
		Number on list 30: bis(α,α-dimethylbenzyl) peroxide
REACH - Candidate List of Substances of Very High Concern for Authorization (Article 59).	:	Number on list 75: bis(α,α-dimethylbenzyl) peroxide
Regulation (EU) No 2024/590 on substances that deplete the ozone layer	:	Not applicable
Regulation (EU) 2019/1021 on persistent organic pollutants (recast)	:	Not applicable
Regulation (EU) No 649/2012 of the European Parliament and the Council concerning the export and import of dangerous chemicals	:	Not applicable
REACH - List of substances subject to authorisation (Annex XIV)	:	Not applicable
Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.	H2	ACUTE TOXIC
	P6b	SELF-REACTIVE SUBSTANCES AND MIXTURES and ORGANIC PEROXIDES
	E2	ENVIRONMENTAL HAZARDS
Water hazard class (Germany)	:	WGK 2 obviously hazardous to water Classification according to AwSV, Annex 1 (5.2)
TA Luft List (Germany)	:	5.2.7.1.1: Carcinogenic substance: Class 1: 2 % 98-82-8
Volatile organic compounds	:	Directive 2010/75/EU of 24 November 2010 on industrial and livestock rearing emissions (integrated pollution prevention and control) Volatile organic compounds (VOC) content: 3,5 %

### Other regulations:

The product is subject to the supply restrictions of the Ordinance on the Prohibition of Chemi-

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended

## Magnalux™ VE Hardener Comp. B

Version 1.3  
Revision Date: 10.01.2025

Date of last issue: 01.12.2023  
Date of first issue: 14.12.2022

cals.

Take note of Law on the protection of mothers at work, in education and in studies (Maternity Protection Act - MuSchG).

Take note of Directive 94/33/EC on the protection of young people at work or stricter national regulations, where applicable.

### 15.2 Chemical Safety Assessment

No Chemical Safety Assessment has been carried out for this mixture.

This product is in full compliance according to REACH regulation 1907/2006/EC.

## SECTION 16: Other information

### Full text of H-Statements

H226	: Flammable liquid and vapor.
H242	: Heating may cause a fire.
H302	: Harmful if swallowed.
H304	: May be fatal if swallowed and enters airways.
H312	: Harmful in contact with skin.
H314	: Causes severe skin burns and eye damage.
H315	: Causes skin irritation.
H319	: Causes serious eye irritation.
H331	: Toxic if inhaled.
H335	: May cause respiratory irritation.
H350	: May cause cancer.
H360D	: May damage the unborn child.
H373	: May cause damage to organs through prolonged or repeated exposure if inhaled.
H373	: May cause damage to organs through prolonged or repeated exposure if swallowed.
H411	: Toxic to aquatic life with long lasting effects.

### Full text of other abbreviations

5.2	: Organic Peroxides
Acute Tox.	: Acute toxicity
Aquatic Chronic	: Long-term (chronic) aquatic hazard
Asp. Tox.	: Aspiration hazard
Carc.	: Carcinogenicity
Eye Irrit.	: Eye irritation
Flam. Liq.	: Flammable liquids
Org. Perox.	: Organic peroxides
Repr.	: Reproductive toxicity
Skin Corr.	: Skin corrosion
Skin Irrit.	: Skin irritation
STOT RE	: Specific target organ toxicity - repeated exposure
STOT SE	: Specific target organ toxicity - single exposure
2000/39/EC	: Europe. Commission Directive 2000/39/EC establishing a first list of indicative occupational exposure limit values
2019/1831/EU	: Europe. Commission Directive 2019/1831/EU establishing a fifth list of indicative occupational exposure limit values
DE DFG BAT	: Germany. MAK BAT Annex XIII

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended

## Magnalux™ VE Hardener Comp. B

Version 1.3  
Revision Date: 10.01.2025

Date of last issue: 01.12.2023  
Date of first issue: 14.12.2022

DE DFG MAK	:	Germany. MAK BAT Annex IIa
DE TRGS 900	:	Germany. TRGS 900 - Occupational exposure limit values.
TRGS 903	:	TRGS 903 - Biological limit values
2000/39/EC / TWA	:	Limit Value - eight hours
2000/39/EC / STEL	:	Short term exposure limit
2019/1831/EU / TWA	:	Limit Value - eight hours
2019/1831/EU / STEL	:	Short term exposure limit
DE DFG MAK / MAK	:	MAK value
DE TRGS 900 / AGW	:	Time Weighted Average

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - substance of very high concern; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

### Further information

#### Classification of the mixture:

Org. Perox. F	H242
Acute Tox. 4	H302
Acute Tox. 3	H331
Acute Tox. 4	H312
Skin Corr. 1B	H314

#### Classification procedure:

Based on product data or assessment
Calculation method
Calculation method
Calculation method
Calculation method

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended

## Magnalux™ VE Hardener Comp. B

Version	Revision Date:	Date of last issue: 01.12.2023
1.3	10.01.2025	Date of first issue: 14.12.2022

---

Eye Dam. 1	H318	Calculation method
Carc. 1B	H350	Calculation method
Repr. 1B	H360D	Calculation method
STOT SE 3	H335	Calculation method
STOT RE 2	H373	Calculation method
Aquatic Chronic 2	H411	Calculation method

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

It is recommended that each customer or recipient of this Safety Data Sheet (SDS) study it carefully and consult resources, as necessary or appropriate, to become aware of and understand the data contained in this SDS and any hazards associated with the product. This information is provided in good faith and believed to be accurate as of the effective date herein. However, no warranty, express or implied, is given. The information presented here applies only to the product as shipped. The addition of any material can change the composition, hazards and risks of the product. Products shall not be repackaged, modified, or tinted except as specifically instructed by the manufacturer, including but not limited to the incorporation of products not specified by the manufacturer, or the use or addition of products in proportions not specified by the manufacturer. Regulatory requirements are subject to change and may differ between various locations and jurisdictions. The customer/buyer/user is responsible to ensure that his activities comply with all country, federal, state, provincial or local laws. The conditions for use of the product are not under the control of the manufacturer; the customer/buyer/user is responsible to determine the conditions necessary for the safe use of this product. The customer/buyer/user should not use the product for any purpose other than the purpose shown in the applicable section of this SDS without first referring to the supplier and obtaining written handling instructions. Due to the proliferation of sources for information such as manufacturer-specific SDS, the manufacturer cannot be responsible for SDSs obtained from any other source.

DE / EN