

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended

SherCor™ Cable Flex 1 Comp. B

Version
1.1

Revision Date:
11.01.2025

Date of last issue: 15.12.2022
Date of first issue: 15.12.2022

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : SherCor™ Cable Flex 1 Comp. B
Product code : 000000000000032422

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Sub-stance/Mixture : Coatings and paints, thinners, paint removers
Recommended restrictions on use : Reserved for industrial and professional use.

1.3 Details of the supplier of the safety data sheet

Company : Sherwin-Williams Coatings
Deutschland GmbH
Rieter Tal 1
71665 Vaihingen / Enz
Telephone : +4970421090
E-mail address of person responsible for the SDS : SDS-DE@sherwin.com

1.4 Emergency telephone

National advisory body/Poison Center

Telephone number: Not available

Supplier

Telephone number: +49 (0) 7042 109-0

Hours of operation: Emergency contact available 24 hours a day

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

| | |
|---------------------------------------|--|
| Respiratory sensitization, Category 1 | H334: May cause allergy or asthma symptoms or breathing difficulties if inhaled. |
| Skin sensitization, Category 1 | H317: May cause an allergic skin reaction. |

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended

SherCor™ Cable Flex 1 Comp. B

Version
1.1

Revision Date:
11.01.2025

Date of last issue: 15.12.2022
Date of first issue: 15.12.2022

2.2 Label elements

Labeling (REGULATION (EC) No 1272/2008)

Hazard pictograms :



Signal Word : Danger

Hazard Statements : H317 May cause an allergic skin reaction.
H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

Precautionary Statements : **Prevention:**

P261 Avoid breathing mist or vapors.
P280 Wear protective gloves.
P284 Wear respiratory protection.

Response:

P304 + P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P333 + P313 If skin irritation or rash occurs: Get medical advice/ attention.
P342 + P311 If experiencing respiratory symptoms: Call a POISON CENTER/ doctor.

Hazardous ingredients which must be listed on the label:

Reaction product of 1,6-diisocyanatohexane homopolymer and (3-mercaptopropyl) trimethoxysilane
m-tolylidene diisocyanate

Additional Labeling

EUH211 Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

EUH204 Contains isocyanates. May produce an allergic reaction.

"As from 24 August 2023 adequate training is required before industrial or professional use."

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended

SherCor™ Cable Flex 1 Comp. B

Version 1.1
Revision Date: 11.01.2025

Date of last issue: 15.12.2022
Date of first issue: 15.12.2022

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Components

| Chemical name | CAS-No. EC-No. Index-No. Registration number | Classification | Concentration (% w/w) |
|---|--|--|--------------------------|
| Reaction product of 1,6-diisocyanatohexane homopolymer and (3-mercaptopropyl) tri-methoxysilane | 192526-20-8 01-2120768758-32-XXXX | Skin Sens. 1A; H317 Aquatic Chronic 4; H413 | >= 0,25 - < 1 |
| m-tolylidene diisocyanate | 26471-62-5 247-722-4 615-006-00-4 01-2119454791-34-XXXX | Carc. 2; H351 Acute Tox. 1; H330 Eye Irrit. 2; H319 STOT SE 3; H335 Skin Irrit. 2; H315 Resp. Sens. 1; H334 Skin Sens. 1; H317 Aquatic Chronic 3; H412 specific concentration limit Resp. Sens. 1; H334 >= 0,1 % | >= 0,1 - < 0,25 |

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first-aid measures

- General advice : Move out of dangerous area.
Show this material safety data sheet to the doctor in attendance.
Do not leave the victim unattended.
- If inhaled : If unconscious, place in recovery position and seek medical advice.
If symptoms persist, call a physician.
- In case of skin contact : If on skin, rinse well with water.
- In case of eye contact : Flush eyes with water as a precaution.
Remove contact lenses.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended

SherCor™ Cable Flex 1 Comp. B

Version
1.1

Revision Date:
11.01.2025

Date of last issue: 15.12.2022
Date of first issue: 15.12.2022

Protect unharmed eye.
Keep eye wide open while rinsing.
If eye irritation persists, consult a specialist.

If swallowed : Keep respiratory tract clear.
Do not give milk or alcoholic beverages.
Never give anything by mouth to an unconscious person.
If symptoms persist, call a physician.

4.2 Most important symptoms and effects, both acute and delayed

Symptoms : There are no data available on the mixture itself. Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS] See Sections 2 and 3 for details. Exposure to component solvent vapour concentrations in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and, in extreme cases, loss of consciousness. Solvents may cause some of the above effects by absorption through the skin. Repeated or prolonged contact with the mixture may cause removal of natural fat from the skin, resulting in non-allergic contact dermatitis and absorption through the skin. If splashed in the eyes, the liquid may cause irritation and reversible damage. This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact.

Risks : May cause an allergic skin reaction.
May cause allergy or asthma symptoms or breathing difficulties if inhaled.

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Treat symptomatically.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Unsuitable extinguishing media : High volume water jet

5.2 Special hazards arising from the substance or mixture

5.3 Advice for firefighters

Special protective equipment for fire-fighters : Wear self-contained breathing apparatus for firefighting if necessary.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended

SherCor™ Cable Flex 1 Comp. B

Version
1.1

Revision Date:
11.01.2025

Date of last issue: 15.12.2022
Date of first issue: 15.12.2022

Further information : Standard procedure for chemical fires.
Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Use personal protective equipment.

6.2 Environmental precautions

Environmental precautions : Prevent product from entering drains.
Prevent further leakage or spillage if safe to do so.
If the product contaminates rivers and lakes or drains inform respective authorities.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).
Keep in suitable, closed containers for disposal.

6.4 Reference to other sections

See sections: 7, 8, 11, 12 and 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling : Good housekeeping standards, regular safe removal of waste materials and regular maintenance of spray booth filters will minimise the risks of spontaneous combustion and other fire hazards.

Do not breathe vapors/dust.
Avoid exposure - obtain special instructions before use.
Avoid contact with skin and eyes.
For personal protection see section 8.
Smoking, eating and drinking should be prohibited in the application area.
Dispose of rinse water in accordance with local and national regulations.
Persons susceptible to skin sensitization problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.

Advice on protection against fire and explosion : Normal measures for preventive fire protection.

Hygiene measures : Wash hands before breaks and at the end of workday.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended

SherCor™ Cable Flex 1 Comp. B

Version 1.1
Revision Date: 11.01.2025

Date of last issue: 15.12.2022
Date of first issue: 15.12.2022

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers : Keep container tightly closed in a dry and well-ventilated place. Electrical installations / working materials must comply with the technological safety standards.

Storage class (TRGS 510) : 10

Further information on storage stability : No decomposition if stored and applied as directed.

7.3 Specific end use(s)

Specific use(s) : No data available

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

| Components | CAS-No. | Value type (Form of exposure) | Control parameters | Basis |
|--------------------|---|--|-------------------------------|-------------|
| polyvinyl chloride | 9002-86-2 | BM (Alveolar dust fraction) | 0,5 mg/m3 | DE TRGS 527 |
| | | MAK (measured as the alveolate fraction) | 0,3 mg/m3 | DE DFG MAK |
| | Peak-limit category: 8; II | | | |
| | Further information: Substances that cause cancer in humans or animals or that are considered to be carcinogenic for humans and for which a MAK value can be derived., Damage to the embryo or foetus is unlikely when the MAK value or the BAT value is observed | | | |
| titanium dioxide | 13463-67-7 | AGW (Inhalable fraction) | 10 mg/m3 (Titanium dioxide) | DE TRGS 900 |
| | Peak-limit category: 2;(II) | | | |
| | Further information: When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child | | | |
| | | AGW (Alveolate fraction) | 1,25 mg/m3 (Titanium dioxide) | DE TRGS 900 |
| | Peak-limit category: 2;(II) | | | |
| | Further information: When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child | | | |
| | | MAK (measured as the alveolate fraction) | 0,3 mg/m3 | DE DFG MAK |
| | Peak-limit category: 8; II | | | |
| | Further information: Substances that cause cancer in humans or animals or that are considered to be carcinogenic for humans and for which a MAK value can be derived., Damage to the embryo or foetus is unlikely when the MAK value or the BAT value is observed | | | |

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended

SherCor™ Cable Flex 1 Comp. B

Version
1.1

Revision Date:
11.01.2025

Date of last issue: 15.12.2022
Date of first issue: 15.12.2022

| | | | | |
|---------------------------|---|---------------------------|--------------------------|-------------|
| m-tolylidene diisocyanate | 26471-62-5 | AGW | 0,005 ppm 0,035 mg/m3 | TRGS 430 |
| | Peak-limit category: 1;=4=(I) | | | |
| | Further information: In well-founded cases also a momentary value can be established, that never can be exceeded. This substance will be indicated by = = in combination with an exceeding value., airway sensitizing substance | | | |
| | | AGW (Vapour and aerosols) | 0,005 ppm 0,035 mg/m3 | DE TRGS 900 |
| | Peak-limit category: 1;=4=(I) | | | |
| | Further information: In well-found cases also a momentary value can be established, that never can be exceeded. This substance will be indicated by = = in combination with an exceeding value., Substance sensitizing through the respiratory system | | | |
| | | MAK | 0,001 ppm 0,007 mg/m3 | DE DFG MAK |
| | Peak-limit category: 1; I | | | |
| | Further information: Danger of sensitization of the airways and the skin, Damage to the embryo or foetus is unlikely when the MAK value or the BAT value is observed | | | |
| | | Mow | 0,005 ppm 0,035 mg/m3 | DE DFG MAK |
| | Peak-limit category: 1; I | | | |
| | Further information: Danger of sensitization of the airways and the skin, Damage to the embryo or foetus is unlikely when the MAK value or the BAT value is observed | | | |
| | | TWA | 0,01 mg/m3 (NCO) | 98/24/EC I |
| | Further information: Skin, Dermal and respiratory sensitisation, Binding | | | |
| | | STEL | 0,02 mg/m3 (NCO) | 98/24/EC I |
| | Further information: Skin, Dermal and respiratory sensitisation, Binding | | | |

Biological occupational exposure limits

| Substance name | CAS-No. | Control parameters | Sampling time | Basis |
|---------------------------|------------|--|---|------------|
| m-tolylidene diisocyanate | 26471-62-5 | Sum of 2,4- und 2,6-TDA: 5 µg/g creatinine (Urine) | Immediately after exposition or after working hours | DE DFG BAT |

Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006

| Substance name | End Use | Routes of exposure | Potential health effects | Value |
|--|-----------|--------------------|----------------------------|-----------|
| Reaction product of 1,6-diisocyanatohexane homopolymer and (3-mercaptopropyl) trimethoxysilane | Workers | Inhalation | Long-term systemic effects | 1,7 mg/m3 |
| | Workers | Dermal | Long-term systemic effects | 4,7 mg/kg |
| | Consumers | Inhalation | Long-term systemic effects | 0,3 mg/m3 |

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended

SherCor™ Cable Flex 1 Comp. B

Version
1.1

Revision Date:
11.01.2025

Date of last issue: 15.12.2022
Date of first issue: 15.12.2022

| | | | | |
|--|-----------|--------|----------------------------|-----------|
| | Consumers | Dermal | Long-term systemic effects | 1,7 mg/kg |
|--|-----------|--------|----------------------------|-----------|

Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006

| Substance name | Environmental Compartment | Value |
|--|---------------------------|-------------|
| Reaction product of 1,6-diisocyanatohexane homopolymer and (3-mercaptopropyl) trimethoxysilane | Fresh water | 0,1 mg/l |
| | Intermittent use/release | 1 mg/l |
| | Sea water | 0,01 mg/l |
| | Intermittent use/release | 1 mg/l |
| | Fresh water sediment | 23,28 mg/kg |
| | Sea sediment | 2,33 mg/kg |
| | Sewage treatment plant | 100 mg/l |
| | Soil | 4,58 mg/kg |

8.2 Exposure controls

Personal protective equipment

Eye/face protection : Eye wash bottle with pure water
Safety glasses with side-shields conforming to EN166

Tightly fitting safety goggles

Hand protection

Material : Chemical resistant gloves made of butyl rubber or nitrile rubber category III according to EN 374.

Glove length : Standard glove type.

Guideline : Equipment should conform to EN 374

Material : Protective equipment only chosen according to specific regulatory requirements after a risk assessment.

Remarks : Follow the instructions for use issued by the producer.
Gloves should be discarded and replaced if there is any indication of degradation or chemical breakthrough. Be aware that in daily use the durability of a chemical resistant protective glove can be notably shorter than the break through time measured according to EN 374, due to the numerous outside influences (e.g. temperature). The choice of an appropriate glove does not only depend on its material but also on other quality features and is different from one producer to the other. Barrier creams may help to protect the exposed areas of skin, they should however not be applied once exposure has occurred.
The suitability for a specific workplace should be discussed with the producers of the protective gloves.

Skin and body protection : Protective equipment only chosen according to specific regulatory requirements after a risk assessment.
Equipment should conform to EN 14605

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended

SherCor™ Cable Flex 1 Comp. B

Version
1.1

Revision Date:
11.01.2025

Date of last issue: 15.12.2022
Date of first issue: 15.12.2022

Impervious clothing
Choose body protection according to the amount and concentration of the dangerous substance at the work place.

Respiratory protection : Equipment should conform to EN 14387
General and local exhaust ventilation is recommended to maintain vapor exposures below recommended limits. Where concentrations are above recommended limits or are unknown, appropriate respiratory protection should be worn. Follow OSHA respirator regulations (29 CFR 1910.134) and use NIOSH/MSHA approved respirators. Protection provided by air purifying respirators against exposure to any hazardous chemical is limited. Use a positive pressure air supplied respirator if there is any potential for uncontrolled release, exposure levels are unknown, or any other circumstance where air purifying respirators may not provide adequate protection. When workers are facing concentrations above the exposure limit they must use appropriate certified respirators.

No personal respiratory protective equipment normally required.

Filter type : Combined particulates and organic vapor type (A-P)

Protective measures : In case of insufficient ventilation, wear suitable respiratory equipment.

Environmental exposure controls

Water : The product should not be allowed to enter drains, water courses or the soil.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state : paste

Color : various, colorless

Odor : slight

Odor Threshold : No data available

Upper explosion limit / Upper flammability limit : No data available

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended

SherCor™ Cable Flex 1 Comp. B

Version
1.1

Revision Date:
11.01.2025

Date of last issue: 15.12.2022
Date of first issue: 15.12.2022

Lower explosion limit / Lower flammability limit : No data available

Flash point : > 101 °C
Method: closed cup

Decomposition temperature : Not relevant/applicable due to the nature of the product.

pH : Not applicable substance/mixture is non-soluble (in water)

Viscosity
Viscosity, kinematic : > 20,5 mm²/s (40 °C)

Solubility(ies)
Water solubility : insoluble

Partition coefficient: n-octanol/water : Not relevant/applicable due to the nature of the product.

Vapor pressure : 0,01 hPa

Density : ca. 1,16 g/cm³ (20 °C)

Relative vapor density : No data available

9.2 Other information

Explosives : No dangerous reaction known under conditions of normal use.
Not relevant/applicable due to the nature of the product.

Oxidizing properties : No dangerous reaction known under conditions of normal use.
Not relevant/applicable due to the nature of the product.

Self-ignition : Not relevant/applicable due to the nature of the product.

SECTION 10: Stability and reactivity

10.1 Reactivity

No hazards to be specially mentioned.
No decomposition if stored and applied as directed.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended

SherCor™ Cable Flex 1 Comp. B

Version
1.1

Revision Date:
11.01.2025

Date of last issue: 15.12.2022
Date of first issue: 15.12.2022

10.2 Chemical stability

Stable under normal conditions.
No decomposition if stored and applied as directed.

10.3 Possibility of hazardous reactions

Hazardous reactions : No dangerous reaction known under conditions of normal use.

No decomposition if stored and applied as directed.

10.4 Conditions to avoid

Conditions to avoid : Temperatures greater than recommended storage temperature.

10.5 Incompatible materials

Materials to avoid : Strong acids and strong bases
Strong oxidizing agents

10.6 Hazardous decomposition products

Carbon dioxide (CO₂), carbon monoxide (CO), oxides of nitrogen (NO_x), dense black smoke.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Information on likely routes of exposure : There are no data available on the mixture itself. Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS] See Sections 2 and 3 for details.
Exposure to component solvent vapour concentrations in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and, in extreme cases, loss of consciousness. Solvents may cause some of the above effects by absorption through the skin. Repeated or prolonged contact with the mixture may cause removal of natural fat from the skin, resulting in non-allergic contact dermatitis and absorption through the skin. If splashed in the eyes, the liquid may cause irritation and reversible damage. This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact.

Acute toxicity

Not classified due to lack of data.

Product:

Acute inhalation toxicity : Acute toxicity estimate: > 20 mg/l
Exposure time: 4 h

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended

SherCor™ Cable Flex 1 Comp. B

Version
1.1

Revision Date:
11.01.2025

Date of last issue: 15.12.2022
Date of first issue: 15.12.2022

Test atmosphere: vapor
Method: Calculation method

Components:

Reaction product of 1,6-diisocyanatohexane homopolymer and (3-mercaptopropyl) tri-methoxysilane:

Acute oral toxicity : LD50 Oral (Rat): > 2.000 mg/kg
Method: OECD Test Guideline 423

Acute dermal toxicity : LD50 Dermal (Rat): > 2.000 mg/kg
Method: OECD Test Guideline 402

m-tolylidene diisocyanate:

Acute inhalation toxicity : LC50 (Rat): 0,107 mg/l
Exposure time: 4 h
Test atmosphere: vapor

Skin corrosion/irritation

Not classified due to lack of data.

Product:

Remarks : May cause skin irritation and/or dermatitis.

Serious eye damage/eye irritation

Not classified due to lack of data.

Product:

Remarks : Vapors may cause irritation to the eyes, respiratory system and the skin.

Respiratory or skin sensitization

Skin sensitization

May cause an allergic skin reaction.

Respiratory sensitization

May cause allergy or asthma symptoms or breathing difficulties if inhaled.

Product:

Remarks : Causes sensitization.

Germ cell mutagenicity

Not classified due to lack of data.

Carcinogenicity

Not classified due to lack of data.

Reproductive toxicity

Not classified due to lack of data.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended

SherCor™ Cable Flex 1 Comp. B

Version
1.1

Revision Date:
11.01.2025

Date of last issue: 15.12.2022
Date of first issue: 15.12.2022

STOT-single exposure

Not classified due to lack of data.

STOT-repeated exposure

Not classified due to lack of data.

Aspiration toxicity

Not classified due to lack of data.

11.2 Information on other hazards

Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Further information

Product:

Remarks : No data available

SECTION 12: Ecological information

12.1 Toxicity

Components:

Reaction product of 1,6-diisocyanatohexane homopolymer and (3-mercaptopropyl) trimethoxysilane:

Toxicity to fish : LC50 (Brachydanio rerio (zebrafish)): > 100 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 203

Toxicity to daphnia and other : EC50 (Daphnia magna (Water flea)): > 100 mg/l
aquatic invertebrates
Exposure time: 48 h
Method: OECD Test Guideline 202

Toxicity to algae/aquatic : EC50 (Pseudokirchneriella subcapitata (algae)): > 100 mg/l
plants
Exposure time: 72 h
Method: OECD Test Guideline 201

12.2 Persistence and degradability

No data available

12.3 Bioaccumulative potential

No data available

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended

SherCor™ Cable Flex 1 Comp. B

Version
1.1

Revision Date:
11.01.2025

Date of last issue: 15.12.2022
Date of first issue: 15.12.2022

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

12.6 Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

12.7 Other adverse effects

Product:

Additional ecological information : The product should not be allowed to enter drains, water courses or the soil.

No data available

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : Do not dispose of waste into sewer.
Do not contaminate ponds, waterways or ditches with chemical or used container.
Send to a licensed waste management company.

Contaminated packaging : Empty remaining contents.
Dispose of as unused product.
Do not re-use empty containers.

SECTION 14: Transport information

14.1 UN number or ID number

ADR : Not regulated as a dangerous good
IMDG : Not regulated as a dangerous good
IATA : Not regulated as a dangerous good

14.2 UN proper shipping name

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended

SherCor™ Cable Flex 1 Comp. B

Version
1.1

Revision Date:
11.01.2025

Date of last issue: 15.12.2022
Date of first issue: 15.12.2022

ADR : Not regulated as a dangerous good
IMDG : Not regulated as a dangerous good
IATA : Not regulated as a dangerous good

14.3 Transport hazard class(es)

ADR : Not regulated as a dangerous good
IMDG : Not regulated as a dangerous good
IATA : Not regulated as a dangerous good

14.4 Packing group

ADR : Not regulated as a dangerous good
IMDG : Not regulated as a dangerous good
IATA (Cargo) : Not regulated as a dangerous good
IATA (Passenger) : Not regulated as a dangerous good

14.5 Environmental hazards

Not regulated as a dangerous good

14.6 Special precautions for user

Not applicable

14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII) : Conditions of restriction for the following entries should be considered:
Number on list 3

Number on list 20: dibutyltin di-laurate

Number on list 52: 1,2-Benzenedicarboxylic acid, di-C9-11-branched alkyl esters, C10-rich

Number on list 74: m-tolylidene diisocyanate, hexamethylene-diisocyanate

REACH - Candidate List of Substances of Very High

Number on list 75:
: Not applicable

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended

SherCor™ Cable Flex 1 Comp. B

| | | |
|---------|----------------|---------------------------------|
| Version | Revision Date: | Date of last issue: 15.12.2022 |
| 1.1 | 11.01.2025 | Date of first issue: 15.12.2022 |

Concern for Authorization (Article 59).

Regulation (EU) No 2024/590 on substances that deplete the ozone layer : Not applicable

Regulation (EU) 2019/1021 on persistent organic pollutants (recast) : Not applicable

Regulation (EU) No 649/2012 of the European Parliament and the Council concerning the export and import of dangerous chemicals : Not applicable

REACH - List of substances subject to authorisation (Annex XIV) : Not applicable

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances. : Not applicable

Water hazard class (Germany) : WGK 2 obviously hazardous to water
Classification according to AwSV, Annex 1 (5.2)

TA Luft List (Germany) : 5.2.5: Organic Substances:
Class 1: < 0,01 % 67-56-1, 822-06-0
5.2.7.1.3: Substances toxic to reproduction:
others: < 0,01 % 77-58-7

Volatile organic compounds : Directive 2010/75/EU of 24 November 2010 on industrial and livestock rearing emissions (integrated pollution prevention and control)
Volatile organic compounds (VOC) content: < 0,01 %

Other regulations:

Take note of Law on the protection of mothers at work, in education and in studies (Maternity Protection Act - MuSchG).

Take note of Directive 94/33/EC on the protection of young people at work or stricter national regulations, where applicable.

15.2 Chemical Safety Assessment

No Chemical Safety Assessment has been carried out for this mixture.

This product is in full compliance according to REACH regulation 1907/2006/EC.

SECTION 16: Other information

Full text of H-Statements

H315 : Causes skin irritation.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended

SherCor™ Cable Flex 1 Comp. B

Version 1.1
Revision Date: 11.01.2025

Date of last issue: 15.12.2022
Date of first issue: 15.12.2022

| | |
|------|--|
| H317 | : May cause an allergic skin reaction. |
| H319 | : Causes serious eye irritation. |
| H330 | : Fatal if inhaled. |
| H334 | : May cause allergy or asthma symptoms or breathing difficulties if inhaled. |
| H335 | : May cause respiratory irritation. |
| H351 | : Suspected of causing cancer. |
| H412 | : Harmful to aquatic life with long lasting effects. |
| H413 | : May cause long lasting harmful effects to aquatic life. |

Full text of other abbreviations

| | |
|-------------------|---|
| Acute Tox. | : Acute toxicity |
| Aquatic Chronic | : Long-term (chronic) aquatic hazard |
| Carc. | : Carcinogenicity |
| Eye Irrit. | : Eye irritation |
| Resp. Sens. | : Respiratory sensitization |
| Skin Irrit. | : Skin irritation |
| Skin Sens. | : Skin sensitization |
| STOT SE | : Specific target organ toxicity - single exposure |
| 98/24/EC I | : Europe. Chemical Agents Directive - Annex I: Binding occupational exposure limit values |
| DE DFG BAT | : Germany. MAK BAT Annex XIII |
| DE DFG MAK | : Germany. MAK BAT Annex IIa |
| DE TRGS 527 | : Germany. TRGS 527 - Activities with nanomaterials |
| DE TRGS 900 | : Germany. TRGS 900 - Occupational exposure limit values. |
| TRGS 430 | : Germany. TRGS 430 - Isocyanates |
| 98/24/EC I / STEL | : Limit values Short-term |
| 98/24/EC I / TWA | : Limit values 8 hours |
| DE DFG MAK / Mow | : Momentary value |
| DE DFG MAK / MAK | : MAK value |
| DE TRGS 527 / BM | : Assessment scale |
| DE TRGS 900 / AGW | : Time Weighted Average |
| TRGS 430 / AGW | : Occupational Exposure Limit |

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified;

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended

SherCor™ Cable Flex 1 Comp. B

Version
1.1

Revision Date:
11.01.2025

Date of last issue: 15.12.2022
Date of first issue: 15.12.2022

NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - substance of very high concern; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

Further information

Classification of the mixture:

| | |
|---------------|------|
| Resp. Sens. 1 | H334 |
| Skin Sens. 1 | H317 |

Classification procedure:

| |
|--------------------|
| Calculation method |
| Calculation method |

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

It is recommended that each customer or recipient of this Safety Data Sheet (SDS) study it carefully and consult resources, as necessary or appropriate, to become aware of and understand the data contained in this SDS and any hazards associated with the product. This information is provided in good faith and believed to be accurate as of the effective date herein. However, no warranty, express or implied, is given. The information presented here applies only to the product as shipped. The addition of any material can change the composition, hazards and risks of the product. Products shall not be repackaged, modified, or tinted except as specifically instructed by the manufacturer, including but not limited to the incorporation of products not specified by the manufacturer, or the use or addition of products in proportions not specified by the manufacturer. Regulatory requirements are subject to change and may differ between various locations and jurisdictions. The customer/buyer/user is responsible to ensure that his activities comply with all country, federal, state, provincial or local laws. The conditions for use of the product are not under the control of the manufacturer; the customer/buyer/user is responsible to determine the conditions necessary for the safe use of this product. The customer/buyer/user should not use the product for any purpose other than the purpose shown in the applicable section of this SDS without first referring to the supplier and obtaining written handling instructions. Due to the proliferation of sources for information such as manufacturer-specific SDS, the manufacturer cannot be responsible for SDSs obtained from any other source.

DE / EN